Attorney's Docket No.: 460-010108-US(PAR)

03C0
#3

MAR 0 6 2001

PATENT

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

In re application of:. AKSU et al.   Group No.:
Serial No.: 09/766,035
Filed: 1/19/01   Examiner:
For: A METHOD AND ASSOCIATED DEVICE FOR FILTERING DIGITAL VIDEO IMAGES

Commissioner of Patents and Trademarks
Washington, D.C. 20231

TRANSMITTAL OF CERTIFIED COPY

Attached please find the certified copy of the foreign application from which priority is claimed for this case:

Country   : Finland
Application Number   : 20000120
Filing Date   : 20 January 2000

WARNING: "When a document that is required by statute to be certified must be filed, a copy, including a photocopy or facsimile transmission of the certification is not acceptable." 37 CFR 1.4(f) (emphasis added.)

Reg. No.: 24,622

SIGNATURE OF ATTORNEY
Clarence A. Green

Tel. No.: (203) 259-1800

Type or print name of attorney

Perman & Green, LLP

Customer No.: 2512

P.O. Address

425 Post Road, Fairfield, CT 06430

NOTE: The claim to priority need be in no special form and may be made by the attorney or agent if the foreign application is referred to in the oath or declaration as required by § 1.63.

CERTIFICATE OF MAILING/TRANSMISSION (37 CFR 1.8a)

I hereby certify that this correspondence is, on the date shown below, being:

☑ MAILING
deposited with the United States Postal Service with sufficient postage as first class mail in an envelope addressed to the Commissioner of Patents and Trademarks, Washington, D.C. 20231

Date: 3/1/01

☐ FACSIMILE
transmitted by facsimile to the Patent and Trademark Office

Signature
DEBORAH J. CLARK
(type or print name of person certifying)

(Transmittal of Certified Copy [5-4]

PATENTTI- JA REKISTERIHALLITUS
NATIONAL BOARD OF PATENTS AND REGISTRATION

Helsinki 13.12.2000

E T U O I K E U S T O D I S T U S
P R I O R I T Y   D O C U M E N T

Hakija Applicant	**Nokia Mobile Phones Ltd** **Espoo**
Patenttihakemus nro Patent application no	20000120
Tekemispäivä Filing date	20.01.2000
Kansainvälinen luokka International class	H04N
Keksinnön nimitys Title of invention	

"A method for filtering digital video images"
(Menetelmä digitaalisten videokuvien suodattamiseksi)

CERTIFIED COPY OF PRIORITY DOCUMENT

Täten todistetaan, että oheiset asiakirjat ovat tarkkoja jäljennöksiä patentti- ja rekisterihallitukselle alkuaan annetuista selityksestä, patenttivaatimuksista, tiivistelmästä ja piirustuksista.

This is to certify that the annexed documents are true copies of the description, claims, abstract and drawings originally filed with the Finnish Patent Office.

Marketta Tehikoski
Apulaistarkastaja

Maksu	300,-	mk
Fee	300,-	FIM

A method for filtering digital video images

The present invention relates to a method for removing blocking arte-
facts from a frame of a digital video signal, which has been coded by
5   blocks and then decoded, the coding method for a block being selected
according to a predetermined set of coding types, in which method at
least one pixel is selected for examination from at least one side of a
block boundary, and a value of at least one pixel selected for examina-
tion is corrected by filtering. The present invention relates also to a
10   device for removing blocking artefacts from a frame of a digital video
signal, which has been coded by blocks and then decoded, the coding
method for a block being selected according to a predetermined set of
coding types, which device comprises means for selecting at least one
pixel for examination from at least one side of a block boundary, and a
15   filter for correcting a value of at least one pixel selected for examina-
tion. The present invention relates furthermore to a video encoder
according to the preamble of Claim 22, a video decoder according to
the preamble of Claim 24, a video codec according to the preamble of
Claim 25, and a mobile terminal according to the preamble of Claim 26.
20   The present invention relates furthermore to a storage media for storing
a software program comprising machine executable steps for coding
and decoding a digital video signal by blocks, for selecting the coding
method for a block according to a predetermined set of coding types,
for removing blocking artefacts from a frame of a digital video signal, for
25   selecting at least one pixel for examination from at least one side of a
block boundary, for correcting the value of pixels selected for exami-
nation by filtering.

A transmission system like the one shown in Figure 1 is generally used
30   for transferring a digital video image in compressed form. The video
image is formed of sequential frames. In some prior art video transmis-
sion systems, for example ITU-T H.261/H.263 recommendations, three
frame types are defined: an I-frame (Intra), a P-frame (Predicted or
Inter), and a B-frame (Bi-directional). The I-frame is generated solely on
35   the basis of information contained in the image itself, wherein at the
receiving end, this I-frame can be used to form the entire image. P-
frames are formed on the basis of a preceding I-frame or P-frame,
wherein at the receiving stage a preceding I-frame or P-frame is

2

correspondingly used together with the received P-frame in order to reconstruct the image. The preceding I-frame is also used as a reference frame as will be explained later in this description. In the composition of P-frames, for instance motion compensation is used to

5   compress the quantity of information. B-frames are formed on the basis of the preceding P-frame or I-frame and/or the following P- or I-frame.

The frames are further divided into blocks. One or more such blocks forms a block region. There can generally be four different region types:

10   Intra region, copy region, coded region, and not-coded region. An intra region is a block region in which the blocks are coded independently without reference to any other frame. A copy region consists of blocks which are obtained by copying the content of the reference frame into exactly the same location without any motion compensated prediction.

15   A coded region consists of blocks which are obtained using motion compensated prediction and prediction error coding. The prediction error is a difference between the pixel values of the actual frame and a reconstructed frame which is formed by using coding and decoding in a transmitting system. The prediction error is then coded and sent to a

20   receiver. A not-coded region is obtained using motion compensated prediction only. In fact the not-coded region is equivalent to a copy region if the motion information equals 0. All the block regions of one frame are not necessarily similar types but one frame can comprise block regions which are of different types.

25

A current video frame to be coded comes to the transmission system 10 as input data $I_n(x,y)$. In the differential summer 11 it is transformed into a prediction error frame $E_n(x,y)$ by subtracting from it a prediction frame $P_n(x,y)$ formed on the basis of previous images. The prediction

30   error frame is coded in block 12 in a manner described hereinafter, and the coded prediction error frame is directed to a multiplexer 13. To form a new prediction frame, the coded prediction error frame is also directed to a decoder 14, which produces a decoded prediction error frame $\hat{E}_n(x,y)$ which is summed in a summer 15 with the prediction frame $P_n(x,y)$, resulting in a decoded frame $\hat{I}_n(x,y)$. The decoded frame

35   is saved in a frame memory 16. To code the next frame, the frame saved in the frame memory 16 is read as a reference frame $R_n(x,y)$ and

3

in a motion compensation and prediction block 17 it is transformed into a new prediction frame according to the formula

$$P_n(x,y) = R_n[x + Dx(x,y), y + Dy(x,y)] \qquad (1)$$

The pair of numbers $[Dx(x,y), Dy(x,y)]$ is called the motion vector of the
5   pixel at location (x,y) and the numbers $Dx(x,y)$ and $Dy(x,y)$ are the horizontal and vertical shifts of the pixel. They are calculated in a motion estimation block 18. The set of motion vectors $[Dx(\cdot), Dy(\cdot)]$ consisting of all motion vectors related to the pixels of the frame to be compressed is also coded using a motion model comprising basis functions and
10   coefficients. The coefficient values are coded and directed to the multiplexer 13, which multiplexes them into the same data stream with a coded prediction error frame for sending to a receiver. In this way the amount of information to be transmitted is dramatically reduced. The basis functions are known to both the encoder and the decoder. Some
15   frames can be partly or entirely so difficult to predict that it is not practical to use motion compensated prediction when coding them. These frames or parts of frames are coded using so-called intracoding without prediction, and therefore it is not necessary to send motion vector information relating to them to the receiver.

20

In the receiver system 20, a demultiplexer 21 separates the coded prediction error frames and the motion information transmitted by the motion vectors and directs the coded prediction error frames to a decoder 22, which produces a decoded prediction error frame $\hat{E}_n(x,y)$,
25   which is summed in a summer 23 with the prediction frame $P_n(x,y)$ formed on the basis of a previous frame, resulting in a decoded frame $\hat{I}_n(x,y)$. The decoded frame is directed to an output 24 of the decoder and at the same time saved in a frame memory 25. When decoding the next frame, the frame saved in the frame memory is read as a refer-
30   ence frame and transformed into a new prediction frame in the motion compensation and prediction block 26, according to formula (1) presented above.

The coding method applied in block 12 to the coding of the prediction
35   error frame or to the intracoding of a frame or part of a P-frame to be sent without prediction, is generally based on a transformation, the

4

most common of which is Discrete Cosine Transformation, DCT. The frame is divided into adjacent blocks sized e.g. 8 x 8 pixels. In coding and decoding, the blocks are processed independent of one another. The transformation is calculated for the block to be coded, resulting in a

5   series of terms. The coefficients of these terms are quantized on a discrete scale in order that they can be processed digitally. Quantization causes rounding errors, which can become visible in an image reconstructed from blocks so that there is a discontinuity of pixel values at the boundary between two adjacent blocks. Because a certain decoded

10   frame is used for calculating the prediction frame for the next frames, the errors can be propagated in sequential frames, thus causing visible edges in the image reproduced by the receiver. Image errors of this type are called blocking artefacts.

15   Some prior art methods are known for removing blocking artefacts. These methods are characterized by the following features:

- determining which pixel requires value correction in order to remove the blocking artefact,

20

- determining a suitable low-pass filtering for each pixel to be corrected, based on the values of other pixels contained by a filtering window placed around the pixel,

25   - calculating a new value for the pixel to be corrected, and

- rounding the new value to the closest digitized pixel value.

Factors that influence the selection of a filter and the decision to use

30   filtering can be, for example, the difference between the values of pixels across the block boundary, the size of the quantization step of the coefficients received as the transformation result, and the difference of the pixel values on different sides of the pixel being processed.

35   It has been found that the prior art methods also tend to remove lines of the image that should really be part of it. On the other hand, the prior art methods are not always capable of removing all blocking artefacts.

5

The objective of the present invention is to present a new kind of filtering arrangement for removing blocking artefacts. The invention also has the objective that the method and device according to it operate more reliably and efficiently than prior art solutions.

5   The method according to the invention is intended to adjust filtering parameters according to the type of blocks whose boundary is to be filtered. Different filtering parameters are chosen according to the type of block on either side of the boundary in order to yield an improved

10   filtering result.

The objectives of the invention are achieved by adapting the selection of pixels for filtering and the filtering process more flexibly than before to the features of the frame and the environment of the filtering point

15   and by taking into account the nature/type of the blocks to be filtered.

The method according to the invention for removing blocking artefacts from a frame that has been coded by blocks, in which method at least one pixel from at least one side of the block boundary is selected for

20   examination, is characterized in that the filtering applied on the block boundary depends on the block types of the frame in the environment of the block boundary.

The invention also relates to a device for implementing the method

25   according to the invention. The device according to the invention is characterized in that the filter has been arranged to operate adaptively according to the block types of the frame in the environment of the block boundary.

30   The encoder according to the invention is characterized in that the filter has been arranged to operate adaptively according to the block types of the frame in the environment of the block boundary. The decoder according to the invention is characterized in that the filter has been arranged to operate adaptively according to the block types of the

35   frame in the environment of the block boundary. The codec according to the invention is characterized in that the filter has been arranged to operate adaptively according to the block types of the frame in the environment of the block boundary. The mobile terminal according to the

6

invention is characterized in that the filter has been arranged to operate adaptively according to the block types of the frame in the environment of the block boundary. The storage media according to the invention is characterized in that the software program further comprises machine executable steps for filtering adaptively according to the block types of the frame in the environment of the block boundary.

5

Because blocking artefacts only occur at block boundaries, the filtering according to the invention is only applied to pixels at block boundaries and the immediate vicinity thereof. Edges that are part of the image can reside anywhere in the image area. In order that only pixels containing blocking artefacts are selected for corrective filtering and that the quality of edges that are part of the image is not affected during filtering, the following assumptions have been made in the study that resulted in the invention:

10

15

The changes in pixel values associated with edges that are part of the image, are generally larger than those associated with blocking artefacts, and those edges within the image, where the pixel value change is small do not suffer considerably from the rounding of the pixel value difference caused by filtering.

20

Because the image to be coded is generally divided into blocks both vertically and horizontally, the image contains both vertical and horizontal block boundaries. With regard to vertical block boundaries, there are pixels to the right and left of the boundary, and with regard to horizontal block boundaries, there are pixels above and below the boundary. In general, the location of the pixels can be described as being on a first or a second side of the block boundary. In the filtering method according to the invention, the number of pixels to be corrected, the characteristic features of the filter being used and the size of the filtering window depend on the following factors:

25

30

a)   The type of block on either side of the boundary (inter, copy, coded, not-coded),

35

b)   the difference in pixel values Δ across the block boundary (the difference can be defined in many ways; one definition is $\Delta = |r_1 -$

7

$I_1|$, where r_1 is the value of the pixel on the first side of the block bound-
ary closest to the boundary, and I_1 is the value of the pixel on the sec-
ond side of the block boundary closest to the boundary),

5   c)   the size of the quantization step QP of the coefficients
received as the result of the transformation used in coding, and

d)   differences in pixel values between the pixels on the first
side of the block boundary, and correspondingly between the pixels on
10   the second side of the block boundary.

In the method and device according to the invention, the number of the
pixels to be selected for filtering can vary, and it is not necessarily the
same on different sides of the block boundary. The number of pixels
also depends on the type of block on either side of the boundary.
15   Because the number of pixels is adapted to the general features of the
image information contained by the frame in a particular region accord-
ing to the factors mentioned above, the method produces a better filter-
ing result than that provided by prior art methods. A "better" result in
this context is one in which blocking artefacts are reduced to a greater
20   extent while real edges in the image are affected to a lesser degree.. A
larger amount of blocking artefacts can be removed without weakening
the real image edges unreasonably.

25   In the following, the invention will be described in more detail with
reference to the preferred embodiments and the accompanying draw-
ings, in which

Figure 1   represents a prior art video codec,
30

Figure 2   represents the location of pixels in relation to a block
boundary in the method according to the invention,

Figure 3   represents alternatives for locating the filtering method
35   according to the invention in a video codec,

Figure 4   is a schematic representation of a device for implementing a
method according to the invention,

8

Figure 5   represents a device according to Figure 4 in operation, and

Figure 6   is a schematic representation of a portable teleconferencing
device implementing a method according to the invention.

5

In the above, in connection with the description of the prior art, refer-
ence was made to Figure 1, and so in the following description of the
invention and its preferred embodiments, reference will be made mostly

10   to Figures 2 to 5. The same reference numbers are used for corre-
sponding parts in the figures.

Figure 2 shows the location of the pixels r_1 - r_6 and l_1 - l_6 in relation to a
vertical block boundary 30. To implement the method according to the

15   invention, certain parameters must be specified. The parameter n is the
largest number of pixels to be examined from the block boundary in one
direction, and in the case of Figure 2 its value is 6. It is practical to
select the value of the parameter n so that it has a certain relation to
both the difference of the pixel values Δ across the block boundary and

20   to the size of the quantization step QP of the coefficients received as
the result of image coding. Furthermore, the value of the parameter n is
advantageously smaller than or equal to the number of pixels in the
block in the direction of examination to avoid possible blocking artefacts
associated with previous block boundaries spreading to the block

25   boundary under examination. The following definition is recommended
for use in a preferred embodiment of the invention applied to image
blocks comprising 8x8 pixels:

$$n = \begin{cases} 0 & & \Delta \geq 2.00\alpha \\ 1 & 1.50\alpha \leq & \Delta < 2.00\alpha \\ 2 & 1.00\alpha \leq & \Delta < 1.50\alpha \\ 3 & 0.66\alpha \leq & \Delta < 1.00\alpha \\ 4 & 0.40\alpha \leq & \Delta < 0.66\alpha \\ 5 & 0.25\alpha \leq & \Delta < 0.40\alpha \\ 6 & 0 \leq & \Delta < 0.25\alpha \end{cases} \quad , \qquad (2)$$

30

9

wherein $\alpha = QP \cdot \log(QP)$. If QP has a different value in blocks on different sides of the block boundary, the smaller value of QP is used in calculation, as well as in all cases presented hereinafter, in which a definition includes reference to one QP value only. The invention does not

5   limit the determination of the value of parameter n, but according to the guidelines of the equation (2) it is advantageous that its value is generally higher when the difference of pixel values Δ across the block boundary is small in comparison to the size of the quantization step QP of the coefficients received as the result of the coding transformation. If

10   the difference between the pixel values Δ is large, there is a high probability that there is a real image edge at the block boundary, and in this case the pixels are preferably not examined for filtering at all (n=0).

In the next step of the filtering method according to the invention region

15   type information concerning the two neighbouring blocks is examined, *i.e.* the type of the blocks on both sides of the block boundary in question. According to the region type information the value of the parameter n may further be limited (truncated) to provide even better results for removing the blocking artefacts. The region type information is included

20   *e.g.* in the coded information of pixels of one block wherein that information is maintained, or temporarily stored, during the decoding of the information of the block until a truncated value n_{tr} of parameter n is defined.

25   Table 1 shows the truncation values according to an advantageous embodiment of the present invention. Table 1 applies in a situation where the maximun value of n is 6, and, of course, different truncated values would be appropriate in situations where this maximum value is other than 6. These truncation values are used for the first and second

30   sides of the block boundary depending on the region type of the block on the first side of the block boundary and on the region type of the block on the second side of the block boundary.

10

type of the Block on the First side of a boundary	type of the Block on the Second side of a boundary							
	INTRA		COPY		CODED		NOT_CODED	
INTRA	n	n	2	2	n	4	n	2
COPY	2	2	2	2	2	4	2	2
CODED	4	n	4	2	4	4	4	2
NOT_CODED	2	n	2	2	2	4	2	2

TABLE 1

Each cell of Table 1 corresponding to a particular region type combina-tion is split into two parts. The value on the left gives the truncation
5 value *trval* for the first side of the block boundary and the value on the right gives the truncation value *trval* for the second side of the bound-ary. If the value of the parameter 'n' exceeds the value given in Table 1, 'n' is truncated to the truncation value *trval* in Table 1. If, however, the value of the overall activity parameter 'n' does not exceed the value
10 given in Table 1, the value of the parameter n (originally determined from equation (2)) is retained. In Table 1 the symbol "n" indicates that further truncation is not performed and the parameter value is retained. The truncated value n_{tr} for the parameter n can also be presented by the formula:

15

$$n_{tr} = \min(trval, n), \qquad (3)$$

The same table can be used both for filtering across vertical block boundaries (horizontal filtering) by putting "Left"/"Right" in place of
20 "First"/"Second" and for filtering across horizontal block boundaries (vertical filtering) by putting "Bottom"/"Up" in place of "First"/"Second", respectively. Now, the value on the left gives the truncation value for the pixels on the left/below the block boundary and the value on the right gives the truncation value for the pixels on the right/above the
25 boundary.

To further clarify the use of Table 1, an example situation is presented in the following. In this illustrative example situation "horizontal filtering"

11

is performed across a vertical block boundary 30. Assuming that the value for parameter n calculated from equation 2 is *e.g.* 4, the block on the left-hand side of the block boundary 30 in question is Intra type, and the block on the right-hand side of the block boundary 30 in question is

5   Not-coded type, Table 1 indicates that the truncation value for the left-hand side is 'n' and the truncation value for the right-hand side is 2. This means that the 4 pixels closest to the block boundary (=the calculated value of n) are selected for filtering from the left-hand side of the boundary, and 2 pixels closest to the block boundary (=the truncated

10 value of n) are selected from the right-hand side for filtering.

Another example situation is presented in the following. In this illustrative example situation "horizontal filtering" is performed across a vertical block boundary 30. Assuming that the value for parameter n calculated

15 from equation (2) is *e.g.* 4, blocks on both sides of the block boundary 30 in question are Copy type, Table 1 indicates that the truncation value for the left-hand side is 2 and the truncation value for the right-hand side is 2. This means that the 2 pixels closest to the block boundary (=the truncated value of n) are selected for filtering from the

20 left-hand side of the boundary, and 2 pixels closest to the block boundary (=the truncated value of n) are selected from the right-hand side for filtering.

For bidirectionally predicted frames (B-frames), truncation of the

25 parameter n is not applied because there is no unique block type information.

The next step in the filtering method according to the invention is to determine the values of the parameters d_l and d_r, which represent

30 activity, or the differences of pixel values between pixels on one side of the block boundary. A preferred definition for d_r is the following:

$d_r = 6$, if $|r_1 - r_j| \leq \beta/j$ with all $j \in [1,6]$,
otherwise: $d_r = i$, where i fulfils the conditions

35                    $i \in [l, n_{tr}]$,   (4)
              $|r_1 - r_{i-1}| > \beta/i$, and
              $|r_1 - r_j| \leq \beta/j$ with all $j \in [l,i]$.

12

Here, the auxiliary parameter $\beta = 4 \cdot \log(QP)$. The value of parameter d_l is determined similarly, except that all r's are replaced by l's and the corresponding truncated value n_{tr} for the parameter n must be used.

5 The number 6 appears in definition (4) because the highest possible value of n is 6 according to equation (2). If n is defined differently, but the parameters d_r and d_l are defined according to definition (4), the number 6 must be replaced by the highest possible value of n according to the new definition.

10 With regard to the invention, it is advantageous that the values of the parameters d_r and d_l are calculated independent of one another, because the image information contained by the frame can be different on different sides of the block boundary. The invention does not limit the definition of parameters d_r and d_l, but according to the guidelines of

15 definition (4) it is advantageous that these parameters are used to limit the blocking artefact processing relatively close to the block boundary, if there is a real image edge near the block boundary. The essential features of definition (4) can be summarised as follows: the value of parameter d_r (and correspondingly the value of parameter d_l) provides

20 an indication of how many pixels counted from the block boundary have approximately the same value as the pixel at the block boundary.

A high value of parameter n (e.g. 6) indicates that the difference between the pixel values at the block boundary is relatively small com-

25 pared with the general variation of the pixel values within the block. In this case, it is possible that there is a real image edge near the block boundary. By selecting a sufficiently small value of parameter d_r (or d_l), it is possible to restrict the filtering aimed at correcting blocking arte-facts so that it does not have a deteriorating effect on a real image

30 edge close to the block boundary. In some situations, a large number of pixels counted from the block boundary have approximately the same value as the pixel at the block boundary. In that case, definition (4) would give the parameter d_r or (d_l) a relatively high value. However, if there is a clear discontinuity in pixel values between the blocks, the

35 parameter n has a small value and the truncated value n_{tr} is used in the definition (4) which make sure that an unreasonably high value is not selected as the value of the parameter d_r (or d_l). Otherwise, a rela-

13

tively high value of the parameter d_r (or d_l) would result in unnecessary filtering.

If blocks on both sides of the block boundary are Intra-type blocks, the
5   truncation has no effect on the selection of the parameter values n, d_r and d_l. On the other hand, if at least one of the blocks has a type other than Intra, the truncation of the value n according to the formula (3) may limit the number of pixels filtered. This has the advantage that the block boundaries are not smoothed too much.

10

In addition, the largest possible number of pixels to be filtered must be decided, *i.e.* filtering window. This does not have a notation of its own in Figure 2, but it can be e.g. 3, which means that filtering can only be used to correct the value of the pixels r_1, r_2, r_3, l_1, l_2 and l_3.

15

When the values of the parameters n, n_{tr}, d_r and d_l have been determined, filtering is carried out using a suitable filter. The invention does not limit the kind of filter that can be used, but a filtering arrangement that has been found preferable, will be described in the following. Filter-
20   ing is used to determine a new value for the pixels selected for filtering. In a preferred embodiment of the invention, a new pixel value is determined for a given pixel by calculating the mean of the pixel values that appear in a filtering window.. In the preferred embodiment, the filtering window is symmetrical with regard to the pixel to be filtered and con-
25   tains, in addition to the pixel to be filtered, one, two or three pixels from its both sides, depending on the values of the parameters d_r and d_l as described hereinafter. Of course these are only examples and other values could be chosen in situations where n, n_{tr}, d_r and d_l are defined differently. The calculated mean value is rounded to the closest digit-
30   ized pixel value, whereby it becomes the new value of the filtered pixel.

Table 2 shows the determination of the width of the filtering window for the pixels r_1, r_2 and r_3 according to the value of parameter d_r in a pre-ferred embodiment of the invention. The values of the pixels l_1, l_2 and l_3
35   are determined in the same manner according to the value of the parameter d_l. In the table, X means that the pixel in question is not fil-tered at all, and the number means that the filtering window includes a number of pixels shown by the number from each side of the pixel

14

being examined. Among other things, Table 2 shows that for filtering to be applied to any pixel, parameters d_r and d_l must both have a value greater than 1.

d_r ($d_l > 1$)	r_1	r_2	r_3
1	X	X	X
2	1	X	X
3	1	1*	X
4	2	2	X
5	2	2	2**
6	3 or 2***	3	3

5

*   the filtered value of pixel r_1 is used for filtering of pixel r_2

**   the filtered values of pixels r_1 and r_2 are used for filtering pixel r_3

***   3 if $d_l > 2$, otherwise 2.

10

The above description relates to implementing the filtering on one horizontal part of a pixel row, which part is 12 pixels long and located symmetrically on both sides of a vertical block boundary. The description can be easily generalized to concern vertical parts of pixel columns, which are located symmetrically on both sides of a horizontal block boundary: Figure 2 can be turned 90 degrees counter-clockwise, whereby block boundary 30 becomes horizontal, and the pixels shown in the figure form part of the vertical pixel column so that pixels r_1 - r_6 are the pixels above and pixels l_1 - l_6 are the pixels below. To filter block boundaries throughout the whole frame by applying the method according to the invention, all vertical block boundaries of the frame are examined row by row and all its horizontal block boundaries column by column. The order has no significance at such, and thus all the horizontal block boundaries of the frame could be examined first column by column, and then all the vertical block boundaries row by row. In an advantageous embodiment of the invention the filtering is repeated line by line, *i.e.* the first line of the pixels in the blocks (besides the boundary) is filtered first, then the second line, etc.

15

Figure 3 shows at which points the prior art image codec can be improved by applying filtering according to the invention. The first alternative is to place the block implementing the filtering according to the invention in the output of the decoder of the receiver as illustrated by

5   reference number 31. In this case, block boundaries in the video frame are only filtered after decoding of all blocks within the frame. This requires block type information to be stored for all the blocks in one frame. Another alternative is to place the block carrying out the filtering according to the invention in the receiver before the point at which the

10   decoded frame is directed to the frame memory 25 for forming a prediction frame, as illustrated by reference number 32. In this case block type information for all blocks within the frame must also be stored, as block boundary filtering is still performed after decoding and reconstructing the entire frame. However, this alternative has the advantage

15   that the removal of blocking artefacts also has an effect on the formation of a prediction frame, whereby blocking artefacts in one frame are not propagated via the prediction frame to the next frames. In order to achieve the last mentioned effect, the block performing filtering according to the invention can be placed before the frame memory 25 or after

20   it, but the location shown by reference number 32 is preferred, because when applied at this stage, the filtering influences simultaneously the frame to be output by the receiving decoder and the frame to be saved in the memory. In the transmitter, the block carrying out filtering according to the invention can be placed as shown by reference numbers 33

25   and 34 before the frame memory 16 or after it, if it is desired that the invention is also applied to producing a corrected prediction frame at the transmission end.

The block carrying out the filtering according to the invention is particu-

30   larly advantageously implemented in a digital signal processor or a corresponding device suited for processing a digital signal, which can be programmed to apply predetermined processing functions to the signal received as input data. At the programming stage of the digital signal processor, the definitions 35 - 39 are saved according to Figure 4 for

35   calculating the parameters that control filtering. During operation according to Figure 5, the frame is saved temporarily in the register 41, so that it can be processed in the signal processor pixel by pixel. A number of pixels indicated by the parameter n_{tr} are selected from the

16

frame as the pixels to be examined 42 at a given instant from each side of a certain point of a certain block boundary, the d-parameters 43 are calculated, filtering 44 is performed, and these measures are repeated, until all boundaries of all blocks have been filtered/processed, after

5   which the frame can be output from the register 41 and a new frame saved for processing. The measures according to Figures 4 and 5 can be carried out in a separate signal processor or they can be part of the operation of such a general processor which also contains other arrangements for signal processing.

10

A storage media can be used for storing a software program comprising machine executable steps for performing the method according to the invention. Then in an advantageous embodiment of the invention the software program can be read from the storage media to a device com-

15   prising programmable means, *e.g.* a processor, for performing the method of the invention.

The invention can be modified without departing from the scope defined by the claims hereinafter, using the capabilities of a person skilled in

20   the art without actual inventive steps. For example, the parameter Δ can be calculated using the formula $\Delta = |(r_1 + r_2) - (l_1 + l_2)|$ or some other formula regarded as suitable. The definitions of other parameters above have also been intended as examples only. A particularly advantageous use of the invention is in mobile teleconferencing applications,

25   digital television receivers and other devices that at least receive and decode digital video image.

Figure 6 shows a mobile terminal 46 intended for use as a portable teleconferencing device and applying the deblocking filter method

30   according to the invention. The mobile terminal 46 comprises advantageously at least display means 47 for displaying images, audio means 48 for audio information, keyboard 49 for inputting *e.g.* user commands, radio part 50 for communicating with mobile network (not shown), processing means 51 for controlling the operation of the device, memory

35   means 52 for storing information, and preferably a camera 53 for taking images.

17

The present invention is not solely restricted to the above presented embodiments, but it can be modified within the scope of the appended claims.

Claims:

1.   A method for removing blocking artefacts from a frame of a digital video signal, which has been coded by blocks and then decoded, the

5   coding method for a block being selected according to a predetermined set of coding types, in which method at least one pixel (n) is selected for examination from at least one side of a block boundary (30), and a value of at least one pixel selected for examination is corrected by filtering, **characterized** in that the filtering applied on the block

10   boundary depends on the block types of the frame in the environment of the block boundary (30).

2.   A method according to Claim 1, **characterized** in that the number of pixels (n) selected for examination depends on the image content of the frame in the environment of the block boundary (30), and that the

15   number of pixels (n) selected for examination further depends on the block types of the frame in the environment of the block boundary (30).

3.   A method according to Claim 2, **characterized** in that the number of pixels selected for examination depends on the size of the quantization step of the coefficients used in the coding of the blocks.

20   4.   A method according to Claim 3, **characterized** in that the number of pixels (n) selected for examination is determined by the formula

$$n = \begin{cases} 0 & & \Delta & \geq 2.00\alpha \\ 1 & 1.50\alpha \leq & \Delta & < 2.00\alpha \\ 2 & 1.00\alpha \leq & \Delta & < 1.50\alpha \\ 3 & 0.66\alpha \leq & \Delta & < 1.00\alpha \\ 4 & 0.40\alpha \leq & \Delta & < 0.66\alpha \\ 5 & 0.25\alpha \leq & \Delta & < 0.40\alpha \\ 6 & 0 \leq & \Delta & < 0.25\alpha \end{cases} , \tag{2}$$

wherein $\alpha = QP \cdot \log(QP)$ and QP is the size of the quantization step of the coefficients used in the coding of the blocks.

25   5.   A method according to Claim 2, 3, or 4, **characterized** in that the number of pixels (n) is first defined according to the image content of the frame in the environment of the block boundary (30), and the

19

number of pixels (n) is further truncated according to the block types of the frame in the environment of the block boundary (30).

6.   A method according to Claim 5, **characterized** in that the truncated value (n_{tr}) of the number of pixels (n) is determined by selecting a truncation value (trval) according to the table

Region type of the Block on the First side	Region type of the Block on the Second side							
	INTRA		COPY		CODED		NOT_CODED	
INTRA	n	n	2	2	n	4	n	2
COPY	2	2	2	2	2	4	2	2
CODED	4	n	4	2	4	4	4	2
NOT_CODED	2	n	2	2	2	4	2	2

and using said selected truncation value (trval) with the formula

$$n_{tr} = \min(trval, n), \tag{3}$$

7.   A method according to any preceding Claim, **characterized** in that certain pixels to be filtered are selected from the pixels selected for examination, and a new value is determined for each pixel to be filtered on the basis of pixels that appear in a filtering window set around the pixel.

8.   A method according to Claim 7, **characterized** in that the new value of the pixel to be filtered is the mean value of the pixels that appear in the filtering window.

9.   A method according to Claim 7, **characterized** in that for determining a new value for the pixels to be filtered on the first side of the block boundary, said filtering window is used, and the size of the window is determined by the table

20

d_r (d_l > 1)	r_1	r_2	r_3
1	X	X	X
2	1	X	X
3	1	1*	X
4	2	2	X
5	2	2	2**
6	3 or 2***	3	3

where

    *   the filtered value of pixel r_1 is used for filtering of pixel r_2

5   **   the filtered values of pixels r_1 and r_2 are used for filtering pixel r_3

   ***   3 if d_l > 2, otherwise 2,

wherein an integer parameter d_r indicates activity on the first side of the block boundary, and an integer parameter d_l indicates activity on the

10 second side of the block boundary, r_1, r_2 and r_3 are the three pixels on the first side of the block boundary closest to the boundary in this order, X means that the pixel is not filtered, the number means that in addition to the pixel to be filtered, a quantity of pixels shown by the number are taken to the filtering window from both sides of the pixel to be filtered,

15 and "3 or 2" means "3, if d_l > 2, otherwise 2", and for determining the new value of the pixels to be filtered on the other side of the block boundary, a filtering window defined similarly is used, with the exception that all r's are replaced by l's and vice versa.

    10. A method according to Claim 9, **characterized** in that

20 d_r = 6, if $|r_i - r_j| \leq \beta/j$ with all $j \in [1,6]$,

otherwise: $d_r = i$, where i must meet the conditions

    $i \in [l, n_{tr}]$,

    $|r_i - r_{i+1}| > \beta/i$, and

    $|r_i - r_j| \leq \beta/j$ with all $j \in [l,i]$,

25 wherein the auxiliary parameter $\beta = 4 \cdot \log(QP)$ and QP is the size of the quantization step of the transformation coefficients used in transformation coding of the blocks, and the value of the parameter d_l is determined similarly, with the exception that all r's are replaced by l's.

21

11. A device for removing blocking artefacts from a frame of a digital video signal, which has been coded by blocks and then decoded, the coding method for a block being selected according to a predetermined set of coding types, which device comprises means for selecting at least one pixel (n) for examination from at least one side of a block boundary (30), and a filter for correcting a value of at least one pixel selected for examination, **characterized** in that the filter has been arranged to operate adaptively according to the block types of the frame in the environment of the block boundary (30).

12. A device according to Claim 11, **characterized** in that it comprises means (41) that operate adaptively according to the image content of the frame, for selecting pixels for examination and filtering, and that means (41) for selecting pixels for examination and filtering comprises further means (42) for examining block types of the frame in the environment of the block boundary (30).12. A device according to Claim 11, **characterized** in that it comprises means (42) for selecting the number of pixels for examination depending on the size of the quantization step of the coefficients used in the coding of the blocks.

13. A device according to Claim 12, **characterized** in that the means (42) for selecting the number of pixels for examination comprises means (35) for determining said number of pixels by the formula

$$
n = \begin{cases}
0 & & \Delta \ge 2.00\alpha \\
1 & 1.50\alpha \le & \Delta < 2.00\alpha \\
2 & 1.00\alpha \le & \Delta < 1.50\alpha \\
3 & 0.66\alpha \le & \Delta < 1.00\alpha \\
4 & 0.40\alpha \le & \Delta < 0.66\alpha \\
5 & 0.25\alpha \le & \Delta < 0.40\alpha \\
6 & 0 \le & \Delta < 0.25\alpha
\end{cases}
\tag{2}
$$

wherein $\alpha = QP \cdot \log(QP)$ and QP is the size of the quantization step of the coefficients used in the coding of the blocks.

14. A device according to Claim 11, 12, or 13, **characterized** in that it comprises means (42) for truncating the number of pixels (n) selected for examination on the basis of said block types

22

15. A device according to any of the Claims 11 to 14, **characterized** in that the means (42) for selecting the number of pixels for examination comprises means for defining the number of pixels (n) according to the image content of the frame in the environment of the block boundary (30), and means for truncating the number of pixels (n) according to the block types of the frame in the environment of the block boundary (30).

5

16. A device according to Claim 15, **characterized** in that the means for truncating the number of pixels (n) comprises means for selecting a truncation value (trval) according to the table

Type of the Block on the First side	Type of the Block on the Second side							
	INTRA		COPY		CODED		NOT_CODED	
INTRA	n	n	2	2	n	4	n	2
COPY	2	2	2	2	2	4	2	2
CODED	4	n	4	2	4	4	4	2
NOT_CODED	2	n	2	2	2	4	2	2

10

and using said selected truncation value (trval) with the formula

$$n_{tr} = \min(trval, n),$$ (3).

17. A device according to any of the Claims 11 to 16, **characterized** in that it comprises means (42) for selecting pixels to be filtered from the pixels selected for examination, means (42) for defining a filtering window, and means for determining a new value for each pixel to be filtered on the basis of pixels that appear in a filtering window set around the pixel.

15

18. A device according to Claim 17, **characterized** in that the means for determining a new value for each pixel comprises means for calculating mean values of the pixels that appear in the filtering window.

20

19. A device according to Claim 17, **characterized** in that the means for determining a new value for each pixel comprises means for using said filtering window for the pixels to be filtered on the first side of the

23

block boundary, and means for determining the size of the window by the table

d_r ($d_l > 1$)	r_1	r_2	r_3
1	X	X	X
2	1	X	X
3	1	1*	X
4	2	2	X
5	2	2	2**
6	3 or 2***	3	3

5   where

*   the filtered value of pixel r_1 is used for filtering of pixel r_2

**   the filtered values of pixels r_1 and r_2 are used for filtering pixel r_3

10 ***   3 if $d_l > 2$, otherwise 2,

wherein an integer parameter d_r indicates activity on the first side of the block boundary, and an integer parameter d_l indicates activity on the second side of the block boundary, r_1, r_2 and r_3 are the three pixels on the first side of the block boundary closest to the boundary in this order,

15 X means that the pixel is not filtered, the number means that in addition to the pixel to be filtered, a quantity of pixels shown by the number are taken to the filtering window from both sides of the pixel to be filtered, and "3 or 2" means "3, if $d_l > 2$, otherwise 2", and means for using a filtering window defined similarly for determining the new value of the

20 pixels to be filtered on the other side of the block boundary, with the exception that all r's are replaced by l's and vice versa.

20. A device according to Claim 19, **characterized** in that

$d_r = 6$, if $|r_i - r_j| \leq \beta/j$ with all $j \in [1,6]$,

otherwise: $d_r = i$, where i must meet the conditions

25        $i \in [l, n_{tr}]$,

$|r_i - r_{i+l}| > \beta/i$, and

$|r_i - r_j| \leq \beta/j$ with all $j \in [l,i]$,

24

wherein the auxiliary parameter $\beta = 4 \cdot \log(QP)$ and QP is the size of the quantization step of the transformation coefficients used in transformation coding of the blocks, and the value of the parameter d_i being determined similarly, with the exception that all r's are replaced
5   by l's.

21. A device according to any of the Claims 11 to 20, **characterized** in that it comprises programmable means (42) for selecting pixels from the saved frame as the pixels to be examined, programmable means (45) for selecting the pixels to be filtered from among the pixels to be
10   examined, and programmable means (44) for determining the new value of the pixels to be filtered.

22. A video encoder (10) comprising means (35—44) for coding and decoding a digital video signal by blocks, means for selecting the coding method for a block according to a predetermined set of coding
15   types, which encoder comprises means for selecting at least one pixel (n) for examination from at least one side of a block boundary (30), and a filter for correcting the value of pixels selected for examination, **characterized** in that the filter has been arranged to operate adaptively according to the block types of the frame in the environment of the
20   block boundary (30).

23. A video decoder (20) comprising means (35—44) for removing blocking artefacts from a frame of a digital video signal, which has been coded by blocks and then decoded, the coding method for a block being selected according to a predetermined set of coding types, which
25   video decoder comprises means for selecting at least one pixel (n) for examination from at least one side of a block boundary (30), and a filter for correcting the value of pixels selected for examination, **characterized** in that the filter has been arranged to operate adaptively according to the block types of the frame in the environment of the
30   block boundary (30).

24. A video codec (10, 20) comprising means (35—44) for coding and decoding a digital video signal by blocks, means for selecting the coding method for a block according to a predetermined set of coding types, means for removing blocking artefacts from a frame of a digital
35   video signal, which video codec comprises means for selecting at least

25

one pixel (n) for examination from at least one side of a block boundary (30), and a filter for correcting the value of pixels selected for examination, **characterized** in that the filter has been arranged to operate adaptively according to the block types of the frame in the
5 environment of the block boundary (30).

25. A mobile terminal (46) comprising a video codec (10, 20), which comprises means (35—44) for coding and decoding a digital video signal by blocks, means for selecting the coding method for a block according to a predetermined set of coding types, means for removing
10 blocking artefacts from a frame of a digital video signal, which video codec comprises means for selecting at least one pixel (n) for examination from at least one side of a block boundary (30), and a filter for correcting the value of pixels selected for examination, **characterized** in that the filter has been arranged to operate adaptively
15 according to the block types of the frame in the environment of the block boundary (30).

26. A storage media for storing a software program comprising machine executable steps for coding and decoding a digital video signal by blocks, for selecting the coding method for a block according
20 to a predetermined set of coding types, for removing blocking artefacts from a frame of a digital video signal, for selecting at least one pixel (n) for examination from at least one side of a block boundary (30), for correcting the value of pixels selected for examination by filtering, **characterized** in that the software program further comprises machine
25 executable steps for filtering adaptively according to the block types of the frame in the environment of the block boundary (30).

Abstract:

The invention relates to a method for removing blocking artefacts from the frame of a digital video signal, which has been coded by blocks and then decoded. The coding method for a block is selected according to a pre-determined set of coding types. A certain number of pixels (n) are selected for examination from both sides of a block boundary (30). The value of the pixels selected for examination is corrected by filtering, and the number of pixels (n) selected for examination depends on the image content of the frame in the environment of the block boundary (30)., and on the block types of the frame in the environment of the block boundary (30).

Fig. 5

Fig. 1

Saapunut: 20/ 1/ 0 16:05;
20/01 '00 16:08 FAX 03 2886   03 2886262 -> PATREK ASIAKASPALVELU;   sivu 29
TAMPEREEN PATENT   PRH   ☑029

2

Fig. 2

Fig. 3

Fig. 4

39 FILTER TYPE

38 MAXIMUM NUMBER
OF PIXELS TO BE
FILTERED

37 DEFINITION OF
THE D-PARAMETERS

36 DEFINITION OF
THE TRUNCATED
VALUE FOR N

35 DEFINITION OF
THE NUMBER
OF PIXELS (N)
TO BE EXAMINED

FILTERING

PIXELS NOT TO
BE FILTERED

PIXELS TO
BE FILTERED

CALCULATION
OF THE
D-PARAMETERS

PIXELS TO
BE EXAMINED

SAVING OF
THE FRAME

Fig. 5

MEM 52

CPU 51

RF 50

AUDIO 48

DISPLAY 47

KEYBOARD 49

CODEC 10,20

CAMERA 53

Fig. 6